



INDUSTRIAL DOORS & LOADING BAY EQUIPMENT





“Committed to providing good service and remaining customer focused at all times.”



CONTENTS

| | |
|--------------------------------|----|
| Swing Lip Dock Leveller | 4 |
| Telescopic Dock Leveller | 4 |
| Curtain Dock Shelter | 5 |
| Compression Dock Seal | 5 |
| Inflatable Dock Shelter | 6 |
| Dock House | 6 |
| Sectional Overhead Door | 7 |
| Roller Shutter | 7 |
| Fire Shutter | 8 |
| High Speed Door | 8 |
| Air Door | 9 |
| Accessories | 9 |
| Service | 10 |

SWING LIP DOCK LEVELLER

KEY FEATURES:

- Fully compliant with BS EN 1398.
- 6000KG or 10000KG single axle load.
- Can be supplied for traditional pit mounting, suspended pits or box style for casting in.
- Lip length 400mm – 500mm.
- Single button operation.

OPERATION

The push button is pressed which raises the platform to it's maximum height at which point the leveller lip will swing out. Once the button is released the platform will descend onto the vehicle bed.

To park the leveller the button is pushed again and the platform rises. The lip will swing back underneath the platform and the button can be released allowing the leveller to descend into it's parked position.

TELESCOPIC DOCK LEVELLER

KEY FEATURES:

- Infinite control over extending lip for the most demanding loading scenarios.
- Fully compliant with BS EN 1398.
- 6000KG or 10000KG single axle load.
- Can be supplied for traditional pit mounting, suspended pits or box style for casting in.
- Standard lip lengths of 500mm or 1000mm.

OPERATION

The platform is raised by pushing the up button. The lip is then extended to the desired length using the lip extension button. Then by pressing the down button the platform will descend on to the vehicle bed.





CURTAIN DOCK SHELTER

KEY FEATURES

- Curtains manufactured from a woven material, coated with black PVC, giving the curtain high resistance to tearing.
- Can be supplied with fixed steel or collapsible support frame to reduce the risk of damage from misaligned vehicles.
- Marker stripes to assist with the aligning of reversing vehicles.

OPTIONS

- Split head curtains.
- Numbering.
- Bottom corner pads.
- Shelter support brackets.



COMPRESSION DOCK SEAL

KEY FEATURES

- Foam cushion pads, covered in tear resistant fabric mounted on galvanised steel backing plates.
- Velcro backed for easy, cost effective replacement.
- Marker stripes to assist with the aligning of reversing vehicles.

OPTIONS

- Inflatable head seal to accommodate wider range of vehicle heights.
- Tapered pads to accommodate yard slopes.
- Wear pleats to increase abrasion resistance.

INFLATABLE DOCK SHELTER

KEY FEATURES

- Fully inflatable head and side seals to accommodate wide range of vehicle widths and heights.
- Seals constructed from high tear resistant Cordura.
- Insulated side panels.

OPTIONS

- Dock mounted or ground mounted units.
- Heavy duty galvanised support brackets.
- Profiled details to accommodate various building details.

DOCK HOUSE

KEY FEATURES

- Self contained loading bay enclosure to suit all types of loading bay equipment.
- Bespoke design to suit all types of operation and buildings.
- Only minor building works required for installation.

OPTIONS

- Can be supplied with single skin cladding and every thickness up to 200mm.
- Can be fixed at angle to building or any configuration required.



SECTIONAL OVERHEAD DOOR

KEY FEATURES

- Insulated, double skin cladding panels.
- Track configurations to accommodate all structural and headroom details.
- Doors purpose made to size.
- Manual or electric operation.
- Safety devices comply with EN 13241.

OPTIONS

- Wide choice of RAL colours.
- Several glazing options.

ROLLER SHUTTER

KEY FEATURES

- Cost effective way to secure door openings.
- Available with insulated or uninsulated lath.
- Can be manufactured to all sizes.

OPTIONS

- Wide choice of RAL colours.
- Perforated lath.
- High security options available.



FIRE SHUTTER

KEY FEATURES

- Up to 4 hours fire resistance.
- Suitable for all types of opening.
- Fully controlled descent.
- Manual or electric operation.

OPTIONS

- Audio visual control panel.

HIGH SPEED DOOR

KEY FEATURES

- Suitable for all applications.
- Speeds up to 2.5M/Sec.
- Long life/low maintenance.
- Soft bottom edge.

OPTIONS

- Cleanroom applications.
- Atex compliant if required.
- Emergency escape doors.
- Soft or rigid door blades.
- Wide choice of standard colours.



AIR DOOR

KEY FEATURES

- Total climate separation.
- Prevents dust, odour, moisture and flies.
- Unrestricted access to door opening.
- Low risk of damage from traffic.
- Seal openings up to 7.0M x 7.0M.
- Bespoke design for each application.

OPTIONS

- Compact versions for small openings.
- Igloo versions for freezers.

ACCESSORIES

We offer a full range of accessories to complement our main products, including:-

- Dock bumpers.
- Traffic lights.
- Dock Lights.
- Wheel guides.
- Barriers.
- Wheel chocks.



SERVICE

We offer planned maintenance, emergency call outs, repairs and refurbishment to all brands of the following equipment:-

- Roller shutters.
- Sectional doors.
- Fast acting doors.
- Dock levellers.
- Scissor lifts.
- Vehicle restraints.
- Automatic barriers.
- Spare parts.



Contact us on:
08451 309 355
for a quotation

T: 08451 309355 | W: www.hsdoors.com | E: info@hsdoors.com







T: 08451 309355 | W: www.hsdoors.com | E: info@hsdoors.com

HS Doors, Unit 26, Kencot Close Business Park, Waldrist Way, Erith DA18 4AB